

SAC3FCB-N-W

# SEETRONIC OUTDOOR POWER CONNECTOR

SEETRONIC Outdoor Power Connector



SAC3FCB-N-W

# SEETRONIC OUTDOOR POWER CONNECTOR

## PRODUCT DETAILS

### KEY FEATURES

Lockable three-core power device AC connector with contacts for line, neutral and pre-adapted safety grounding

High current capacity rated at 20A/250V AC

Quick and easy locking system with firm latch lock which does not fall off

IP65 waterproof grade

Can be docked with SAC3FCA-N-W for linking cables

### SPECIFICATIONS

<b>Contacts</b>	2+PE
<b>Rated current</b>	20A
<b>Rated voltage</b>	250V AC
<b>Contact resistance</b>	?5m?
<b>Dielectric strength</b>	4000V DC
<b>Insulation resistance</b>	1000M?
<b>Service life</b>	?1000
<b>Power lin</b>	2.5mm <sup>2</sup> (8mm-12mm)
<b>Wire stripping length</b>	7-8mm
<b>Type of teminals</b>	screw
<b>Shell</b>	PA
<b>Contacts</b>	Cu alloy
<b>Contact surface</b>	Ag
<b>Protection degree</b>	IP65

# SAC3FCB-N-W SEETRONIC OUTDOOR POWER CONNECTOR

Flame-retardant grade

UL94-V0

Temperature range

-30°Cto+80°C