

## SCENIC C1018Z 18X10W RGBW 4IN1 LED PAR WITH MOTORIZED ZOOM FOR INDOOR USE

Scenic C1018Z is a compact and lightweight LED Par designed for live events, club installations and all those indoor applications where colored lights with variable beam are required. The projector is equipped with a motorized zoom controllable by DMX with angle between 10° and 65°. The light source features 18x10W RGBW 4in1 LEDs, designed to create bright and intense colors.

Its main strengths are reliability and flexibility. The first is based on quality and selection of LED chips, the quality of optical lenses and the use of digital processor technology for LED chip temperature and fan speed control in order to preserve LED life and color brilliance. The second point, flexibility, means that users can choose to turn off the fan by renouncing part of luminance and make the fixture totally silent. This could be very useful to rental companies and professionals in all those "on the fly" situations, where total silence is needed (houses of worship, theaters, conference halls, etc.) and do not have silent multicolor fixtures enough or simply because the installation requires more fixtures than those available.

Scenic C1018Z is color at hand, without hassles in any venue.



# SCENIC C1018Z 18X10W RGBW 4IN1 LED PAR WITH MOTORIZED ZOOM FOR INDOOR USE

---

## HIGHLIGHTS

---



### FAN SPEED AND TEMPERATURE CONTROLLED BY DIGITAL PROCESSOR

The digital processor of the SCENIC C1018Z controls the fan speed and the LED temperature so as to avoid overheating of the chip. The user can choose 3 presets depending on how much noise is acceptable according to the different applications (live show, theater, house of worship, conference, etc.).

**FAN0** - the digital processor activates the fan when the LED internal temperature exceeds 40°C (104°F), and the speed is proportional to heat;

**FAN1** - (Silent Mode) completely turns off the fan, and the fixture becomes totally silent. The processor manages the current supplied to the LED so as not to overheat it. This can lead to a reduction in brightness;

**FAN2** - always leaves the fan on. However, the maximum noise does not exceed 43dBA @ 1m.

SCENIC C1018Z

## 18X10W RGBW 4IN1 LED PAR WITH MOTORIZED ZOOM FOR INDOOR USE

---

### 16-BIT ACCURATE DIMMER CONTROL AND FLICKER-FREE OPERATION

Much attention has been dedicated to the quality of Dimmer control so as to offer smooth DMX or Manual control.

Furthermore, since the frequency of LED control is higher than 15kHz, the annoying **flicker effect** is avoided in case of video shooting of the SCENIC 1027 light sources.



### MOTORIZED ZOOM

The zoom function, controllable via DMX or manually set, allows you to adjust the beam angle from 10 ° to 65 °. The mechanical device and electronic control are accurate and allow a silent and smooth movement of the LED projection surface.

# SCENIC C1018Z

## 18X10W RGBW 4IN1 LED PAR WITH MOTORIZED ZOOM FOR INDOOR USE

### PRODUCT DETAILS

#### KEY FEATURES

- High brightness / long lifespan LED chips with high-quality lens
- RGBW 4in1 color mixing
- Flicker-free LED emission for broadcast applications
- DMX-512 control with RDM
- Motorized zoom with beam angle from 10° to 65°
- Advanced dimmer system and strobo effects
- Intelligent fan speed and control with different settings
- Lightweight aluminum housing with all-directional ventilation system

#### SPECIFICATIONS

<b>Light Source</b>	18 x 10W LED
<b>Color System</b>	RGBW 4in1
<b>LED Control</b>	Flicker-free
<b>Motorized Zoom</b>	From 10° to 65°
<b>Light Source Life-Cycle</b>	> 50.000 h
<b>Dimmer</b>	0-100% linear dimming with Sinusoidal Smooth Subdivision Technology
<b>DMX Control Mode</b>	DMX512 7CH/11CH with RDM
<b>Operating Modes</b>	Master/Slave, Sound Active, Manual
<b>Strobe</b>	0-30Hz

# SCENIC C1018Z

## 18X10W RGBW 4IN1 LED PAR WITH MOTORIZED ZOOM FOR INDOOR USE

<b>Cooling System</b>	All-Direction Ventilating System with DSP control (fan is stopped when LED board temperature is under 40°C; it runs when it is over)
<b>Fan Noise</b>	0dB (temp under 40°C); 43.0 dBA @ 0.5m (temp. above 41°C); 46.1 dBA close to fixture
<b>IP Rate</b>	IP20
<b>Working Temperature</b>	Room Temperature between -20°C and 50°C (-4°F to 122°F)
<b>Housing</b>	Aluminum with fine sand wear-resistant spray paint
<b>Operating Voltage</b>	110V-240V / 50-60Hz
<b>Power Consumption</b>	200W max.
<b>Fixture Size (LxD)</b>	Min. Ø228 x 138.5 mm (Ø8.98 x 5.45 in); Max. - bracket included - Ø282 x 253 mm (Ø11.10 x 9.96 in)
<b>Fixture Weight</b>	3,3 kg (7.27 lbs.)
<b>Carton Size (LxHxD)</b>	290 x 290 x 290 mm (11.42 x 11.42 x 11.42 in)
<b>Carton Weight</b>	4,3 kg (9.48 lbs.)