

GS6

6" PASSIVE SUBWOOFER 4 OHM

GS6

6" Passive Subwoofer

Compact 6" Passive Subwoofer, designed for indoor applications, for permanent installations in retail stores, restaurants, hotels, bars, nightclubs and residential spaces.

Designed to match our GF22 and GF82 loudspeakers as a low frequency extension device. The GS6 features a symmetrical load circuit design, this allows it to be connected directly to most standard loudspeakers such as the GF4 and GF6.

Thanks to a built-in low-pass filter, the GS6 does not require any additional EQ or DSP and can be connected to the same speaker line as the satellites with no hassle!



GS6

6" PASSIVE SUBWOOFER 4 OHM

PRODUCT DETAILS

KEY FEATURES

Compact Design

Designed to match our GF22 and GF82 loudspeakers

Built-in low-pass filter

SPECIFICATIONS

Type	Passive Subwoofer
Transducers	6" ferrite woofer
Frequency Response	50Hz-140kHz (-10 dB)
Max.SPL?108dB (calculated using a signal with crest factor 4 (12dB) measured at 1 mt)	
Power handling	120 watt
Nominal Impedance	4 Ohm
Coverage	Omni
Dimensions (WxHxD)	170 x 310 x 310 mm (6,7 x 12,2 x 12,2 in)
Weight	3,2 kg (7 lb)
Material	Birch Plywood
Color	black