

GALA-520XW **5.25" 2-WAY COAXIAL CEILING SPEAKER**

GALA X Series offers powerful and accurate coaxial loudspeakers with woofer diameters ranging from 5,25" to 8", and powers from 20W to 40W RMS. They can be used with standard 70/100V professional amplifiers, and provide transparent and brilliant sound. They are therefore suitable for any application of music distribution at higher volume levels.

The housing of GALA X speakers is made of high quality ABS. They also feature 0.5" Mylar-dome tweeters, polypropylene enforced woofers, and aluminum removable grille, which make these speakers suitable for humid environments.

Installation is very easy, thanks to the quick mounting system with 4 screws. These screws are hidden behind the grill, and offer an elegant and minimalist design. The built-in line transformers allow the use with 70/100V lines, and offer two power taps to better adapt to different speaker arrangement and amplifier powers. They come in white color, but can be painted in any color.

















GALA-520XW 5.25" 2-WAY COAXIAL CEILING SPEAKER

PRODUCT DETAILS

KEY FEATURES

2-Way Coaxial Loudspeaker

5.25" (135 mm) Woofer

20W RMS Power

High Excursion Polypropylene Woofer

Mylar-dome Precision Tweeter

Built-in 70/100V Line Transformer

Quick Mounting System

Paintable Grille and Frame

SPECIFICATIONS

Speaker Type		2-Way Passive, Coaxial
Line Voltage		70V/100V
Line Transformer		Built-in, 2 power taps
100V Power		10W/20W
70V Power		5W/10W
Frequency Response (-10dB)		80Hz-18.5kHz
Sensitivity (1w/1m)		87dB
Woofer		5.25" (135mm), PP cone
Tweeter	0.5" (13mm), Mylar dome	
Housing	PP, paintable	
IP Rate (speaker installed)	IP54	





GALA-520XW **5.25" 2-WAY COAXIAL CEILING SPEAKER**

Mounting	Quick mounting system with 4 screws	
Grille	Perforated steel with acoustic transparent foam inside, paintable	
Color	White	
Cutout Size	Ø 172 mm	
Product Size (WxDxH)	Ø 203 x 90 mm	
Speaker Weight	1.0 kg	
Packing Size (WxDxH)	205 x 95 x 205 mm	
Packing Weight	1,1 kg	

