

GO-SOUND 10A 480 WATT 10" POLYPROPYLENE ACTIVE SPEAKER

Go-Sound series is built with the user in mind. As result of years of experience gathered by Soundsation in portable sound systems, we designed these versatile high-quality speakers with unmatched value and performances. Built in a polypropylene cabinet, sturdy yet compact and lightweight, these active speaker are equipped with Class AB amplifiers, which guarantee reliability and outstanding performances. Mic and line inputs are included to allow the user to connect various audio sources such as microphones, mixers as well as smartphones and tablets. Go-Sound series is an incredible value and the perfect solution in many situations such as parties, presentations, schools, conference and live music, delivering great sound quality, reliability and ease of use.



GO-SOUND 10A

480 WATT 10" POLYPROPYLENE ACTIVE SPEAKER

PRODUCT DETAILS

KEY FEATURES

2-Way Active Speaker

Sturdy polypropylene enclosure yet compact and lightweight

480 Watt class AB power amplifier

10" woofer with 1" compression driver

Balanced microphone/Line inputs XLR + ¼" Jack and line inputs Stereo RCA + Stereo Mini jack ideal to connect smartphones and tablets

XLR line output

Mic/line switch, volume and equalizer (Hi and Low) controls

36 mm standard pole mount

2 side handles and 1 top handle for convenient carrying

Speaker Dimension (WxHxD): 320 x 490 x 260 mm

Weight: 6,4 Kg

SPECIFICATIONS

2-Way active speaker

Woofer 10" with 1.5" voice coil

Compression driver 1" voice coil, 1" throat

Directivity 90° x 50°, asymmetric

Frequency Response [- 3dB] 75Hz - 18KHz

GO-SOUND 10A

480 WATT 10" POLYPROPYLENE ACTIVE SPEAKER

| | |
|------------------------------------|--|
| Frequency Response [- 10dB] | 70Hz - 18KHz |
| Max SPL(Peak) | 112 dB |
| Sensitivity | 93dB |
| Class AB amplifier | |
| Power (Peak/Rated) | 480W/240W |
| Crossover | 3.2KHz, 18dB/Oct. |
| EQ | High (2.5KHz, +/- 12 dB); Low (150Hz, +/- 12 dB) |
| LEDs | Power On (Green), Clip (Red) |
| Power Requirement | 230Vac - 50 Hz |
| Minimum Power Consumption | 130W |
| Power Connector | VDE with T1A-250V Fuse |
| Speaker Dimension (WxHxD) | 320 x 490 x 260 mm |
| Weight | 6,4 Kg |