

GC6T-RNB

6,5" CEILING SPEAKER 70/100V TRASFORMER IN-WALL ROUND BLACK

6,5" Ceiling Speaker

6,5" 2-way passive full range speaker for ceiling and in-wall installation. With a circular frameless grille design and orientable tweeter, GCF6 is the most versatile choice for residential and commercial environments such as apartments, villas, small home theaters, hotels, hospitals, bars and restaurants, corporate buildings.

GCF6 is available in 8 ohm for smaller sized, hi-fi applications as well as in 70/100V version (GCF6T) for large scale distributed sound installations where a very high number of speakers is required.

For optimal performance, depending on power/quantity needs, this speaker can be combined with any KGEAR amplifier (GA201, GA41/41L, GA43/43L, GA46/46L) and subwoofer (GS6, GCF8S, GWF8S). Available in black or white colour, the frameless magnetic grille can also be painted to match any environment.



GC6T-RNB

6,5" CEILING SPEAKER 70/100V TRASFORMER IN-WALL ROUND BLACK

PRODUCT DETAILS

SPECIFICATIONS

| | |
|---|---|
| Type | Passive Fullrange Loudspeaker |
| Transducers | 6,5" coaxial Woven Glass Fiber woofer with 0.75" Mylar dome tweeter |
| Frequency Response | 60Hz-20kHz (-10 db) |
| Max.SPL?110dB (calculated using a signal with crest factor 4 (12dB) measured at 1 mt) | |
| Power handling | 70v (2W 4W 8W 16W) / 100v (4W 8W 16W 32W) |
| Coverage | V. 130° H. 130° |
| Dimensions (Øouter [Øinner] x H) | Ø227 [210] x 87 mm (8.9 [8.3] x 3.4 in) |
| Maximum mounting depth | 94 mm (3.7 in) |
| Weight | 1,52 kg (3.3 lb) |
| Material | ABS |
| IP rating | IP54 |
| Color | Black |