





CM-S54T-K 4" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Drawing on our club loudspeaker manufacturing heritage, the versatile two-way CM-S54T, CM-S56T and CM-S58T produce premium-quality audio. Available in black or white, these new units are perfect for discreet installation in a variety of spaces where reliability is crucial, and the loudspeakers can even be used for some applications outdoors.

These affordable and adaptable new arrivals in the CM Series include a host of features including transformer taps – ideal if you need a professional and adaptable fixed installation solution.



CM-S54T-K

4" SURFACE MOUNT LOUDSPEAKER (COUPLE)

PRODUCT DETAILS

KEY FEATURES

Soft dome tweeter

Newly developed Vortex Bass Accelerator

Flexible 8 ohms impedance

Dust and water resistant

U bracket

Original curved enclosure design

Color: Black

SPECIFICATIONS

Two-way passive, reflex-loaded

Frequency response (- 10 dB, Typical) 95 Hz - 20 kHz

Sensitivity (1W/1m) 87 dB

Nominal Impedance 8 Ω

Power Handling (RMS/Program) 40 W / 80 W * IEC60268-5

Transformer taps 70 V 30 W / 15 W / 7.5 W / 3.75 W

Transformer taps 100 V 30 W / 15 W / 7.5 W

Dispersion 120 °H x 120 °V

Maximum SPL 109 dB (peak) * Calculated from the power handling and sensitivity

LF 4.5" (114 mm) cone

HF 1" (25 mm) silk dome tweeter

Connectors Euroblock (4 pin) × 1 (input +/-, loop-thru

CM-S54T-K

4" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Rigging and Hardware

1 × U-bracket 2 × M6 threaded mounting points on rear

Grille

Punched Aluminum

Enclosure PP

Dimensions (WxHxD) 154.9x250.6x144.5 mm

Weight

3.4 kgs

Environmental IP54