

GPXA

KGEAR SYSTEM 2X18" ACTIVE SUBWOOFER + 4X12" SLIM ARRAY, BLACK

Heavy duty 2 x 18" powered subwoofer combined with GH412 4 x 12" coaxial high efficiency passive array element. PAT® SAT® K-array™ technologies implemented. It can drive a GPX passive system in a stereo/dual mono configuration. Featuring Powersoft™ DSP

and power module with ethernet remote control and Armonia™ control software. Designed for high performance outdoor/indoor applications both for rental and permanent installations for touring, large auditorium, stadia, theme parks and clubs. Weather resistant rugged box.



GPXA

KGEAR SYSTEM 2X18" ACTIVE SUBWOOFER + 4X12" SLIM ARRAY, BLACK

PRODUCT DETAILS

KEY FEATURES

Complete and compact powered system

Powersoft™ power module and DSP

Designed for high performance applications

SPECIFICATIONS

Power Handling	1500W subwoofer + 750W satellite
Peak Power	3000W subwoofer + 1500W satellite
Impedance	4? subwoofer + 8? satellite
Frequency Range	30Hz – 20KHz (-6dB average)
Maximum SPL	140dB (peak) crest factor 4 (12dB) measured at 1 m
Continuos SPL	128dB
Coverage	V.30° - H.90°
Subwoofer	2 x 18" ferrite magnet
Mid High Frequency	4 x 12" coaxial with 1" compression driver ferrite magnet
Analog balanced INPUT	2 x Combo jack-XLR female line
Analog power O	1 x Speakon to drive a GPX Passive System in a stereo configuration
Volume Potentiometer	
RJ45 connector	
Amplifier	4-channel Class D

GPXA

KGEAR SYSTEM 2X18" ACTIVE SUBWOOFER + 4X12" SLIM ARRAY, BLACK

Power	4 x 1500W @4ohm
AC input	100-240V AC @50-60Hz
Max power consumption	500W Rated Load (1/8 Max Output Power)