





## CM-S58T-K 8" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Drawing on our club loudspeaker manufacturing heritage, the versatile two-way CM-S54T, CM-S56T and CM-S58T produce premium-quality audio. Available in black or white, these new units are perfect for discreet installation in a variety of spaces where reliability is crucial, and the loudspeakers can even be used for some applications outdoors.

These affordable and adaptable new arrivals in the CM Series include a host of features including transformer taps – ideal if you need a professional and adaptable fixed installation solution.



# CM-S58T-K

## 8" SURFACE MOUNT LOUDSPEAKER (COUPLE)

### PRODUCT DETAILS

#### KEY FEATURES

Soft dome tweeter

Newly developed Vortex Bass Accelerator

Flexible 8 ohms impedance

Dust and water resistant

U bracket

Original curved enclosure design

Color: Black

#### SPECIFICATIONS

Two-way passive, reflex-loaded

Frequency response (- 10 dB, Typical) 53 Hz - 20 kHz

Sensitivity (1W/1m) 91 dB

Nominal Impedance 8 Ω

Power Handling (RMS/Program) 90 W / 180 W \* IEC60268-5

**Transformer taps 70 V** 60 W / 30 W / 15 W / 7.5 W

**Transformer taps 100 V** 60 W / 30 W / 15 W

Dispersion 100 °H x 100 °V

Maximum SPL 117 dB (peak) \* Calculated from the power handling and sensitivity

**LF** 8" (200 mm) cone

**HF** 1" (25 mm) silk dome tweeter

**Connectors Euroblock (4 pin) × 1 (input)** +/-, loop-thru

CM-S58T-K

# 8" SURFACE MOUNT LOUDSPEAKER (COUPLE)

**Rigging and Hardware**

1 x U-bracket 2 x M6 threaded mounting points on rear

**Grille**

Punched Aluminum

Enclosure PP

Dimensions ( WxHxD) 282.0 x 457.8 x 252.4 mm

**Weight**

7.5 kgs

Environmental IP54