

# 0993970921 AMERICAN PROFESSIONAL II JAZZMASTER NECK, 22 NARROW TALL FRETS, 9.5" RADIUS, ROSEWOOD

Crafted in the same facility as our U.S.-made instruments, the American Professional II Jazzmaster Neck draws from more than sixty years of innovation, inspiration and evolution to meet the demands of today's working player. Our popular Deep "C" neck now sports smooth rolled fingerboard edges and a "Super-Natural" satin finish that provides a supremely comfortable feel. Other features include a 9.5"radius rosewood fingerboard, bone nut and 22 narrow-tall frets for easy bending.

The neck pocket has 4 offset pre-drilled pilot holes so if it is being installed on a standard body, a fifth pilot hole will need to be drilled.

This replacement neck is for a Fender® or Squier® by Fender guitar.

Because Fender genuine replacement necks have not been mounted to guitar bodies, nut slots must be cut by qualified personnel. Other installation processes may be required, such as fret work, fitting the neck to the neck pocket, and other instrument setup procedures. Your local FMIC Authorized Service Center can install genuine replacement necks







#### FRENEXPORT

Via Enzo Ferrari 10 62017 Porto Recanati (MC), Italy info@frenexport.it



# 0993970921 AMERICAN PROFESSIONAL II JAZZMASTER NECK, 22 NARROW TALL FRETS, 9.5" RADIUS, ROSEWOOD

## **PRODUCT DETAILS**

### **KEY FEATURES**

Instrument Type: Jazzmaster®
Neck Material: Maple
Color: Natural
Neck Shape: Deep "C"
Fret Size: Narrow Tall
Number of Frets: 22
Truss Rod: Bi-Flex™
Nut Material: Bone
Neck Mounting: 4-Bolt Offset

### **SPECIFICATIONS**

Fingerboard Radius	9.5" (241 mm)
Nut Width	1.685"
Scale Length	25.5" (648 mm)
Truss Rod Nut	1/8" Hex Adjustment
Neck Thickness	1st Fret820" (20.82 mm), 12th Fret920" (22.86 mm)
Tuner Mounting Config	Dual Guide Pin
Peg Hole Diameter	.404" (10.26 mm)
Headstock Thickness	.540" (13.71 mm)

### FRENEXPORT

Via Enzo Ferrari 10 62017 Porto Recanati (MC), Italy info@frenexport.it